



FH 200s




The FH 200S was carefully designed to work with a wide response, adapting to the most varied types of sound systems, standing out from the mid-bass to the highs with excellent acoustic performance, due to the selection of its components such as bullet and cellulose whizzer cone, which contribute to this product achieving this excellent result, that is, a frequency response of 120hz to 20khz. Live a new experience, listening to your playlist with a fidelity that will amaze your ears.

ELECTRIC PARAMETERS

| RMS POWER | 100 W |
|---|--------------------|
| MUSICAL PROGRAM POWER | 200 W |
| NOMINAL IMPEDANCE | 4 or 8 Ohms |
| RESISTANCE (RE) | 3,4 / 7,2 ohms/VCC |
| NO (EFFICIENCY REFERENCE) | 0,665% |
| SENSITIVITY (@ 1W, 1 m)-Free-Air | 90,245 dB |
| DIAPHRAGM MASS (MMD) | 5,349g |
| TOTAL MASS (MMS) | 5,800 g |
| BL PRODUCT | 4.363 TM |
| MECHANICAL Q (Qms) | 4,654 |
| ELECTRIC Q (Qes) | 1,086 |
| TOTAL Q (Qts) | 0,880 |
| COMPLIANCE (CMS) | 156,993u M/N |
| EQUIVALENT VOLUME (VAS) | 1,609 L |
| FREQUENCY RESPONSE | 120Hz to 20.000Hz |
| RESONANCE FREQUENCY | 166,795 Hz |
| Le @ 10 kHz (COIL INDUCTANCE AT 10 kHz) | 0,1680 mH |
| EFFECTIVE CONE AREA (SD) | 0,0084 Sq.m |
| CONE EXCURSION WITHOUT DISTORTION (X MAX) | - + 3,0 mm |
| FLOW DENSITY IN THE GAP | 10.300 GAUSS |

Thiele-Small parameters are obtained after applying a sinusoidal level of 50 hz for a period of 30 minutes. A tolerance of + - 15% on the specified values is allowed.






MECHANICAL PARAMETERS


| NOMINAL DIAMETER | 5 Inches |
|--------------------------------|-----------------|
| FERRITE MEASURES | 102 X 43 X 14mm |
| COIL DIAMETER | 1.1/4 Inches |
| COIL HEIGHT | 8,5 mm |
| COIL WIRE MATERIAL | CCAW |
| COIL WIRE SECTION | Round |
| COIL SHAPE | *Kapton® |
| GAP HEIGHT | 4,75 mm |
| HOUSING MATERIAL | Steel |
| FERRITE MATERIAL | Barium |
| WEIGHT | 1,20 Kg |
| OCCUPIED VOLUME ON THE CABINET | 0,34 Litros |

CABINETS SUGGESTION

| MODEL - | VOLUME | DUCTS | DUCTS | DUCTS | SYNTONY | (H.P.F) | ATTENUTION |
|---------------|--------|--------|---------|---------|---------|---------|-----------------|
| | LITERS | QUANT. | DIAM. | DEPTH | | | (ACTIVE) |
| VENTED BOX | 5 | 02 | 2"(POL) | 50,1 mm | 150 Hz | 130 Hz | - 24 dB/ Octave |
| | 7 | 02 | 2"(POL) | 28,5 mm | 140 Hz | 120 Hz | - 24 dB/ Octave |



PRODUCT DIMENSIONS



www.taramps.com.br

WARRANTY TERM

When all our products are produced, they undergo rigorous evaluations, in each construction process until they are packaged, however, if any type of abnormality is detected, when opening the package, it must be sent to one of our authorized service stations, or directly to the factory, if there is not an authorized technitian in your region. **Each and every product must undergo a technical evaluation so that the defect is identified and proven.**

The product has a warranty of 15 (fifteen) months after the issuance of the invoice, with the legal warranty of 90 days, provided for in article 26, item II, of law No. 8078/90 (Brazilian consumer protection code).

Warranty Conditions:

The product must be installed correctly, by a specialized professional, as well as respecting the product characteristics.

The customer will **NOT** have the warranty when:

- Exceed the period of 15 (fifteen) months.
- Damages incurred are caused by; transport or handling accident, or humidity.
- Defects caused by improper installation.
- Malfunctions in product parts (torn cone/dust cap, bent or broken speaker housing).
- Coils burned out by excessive power or extreme distortion conditions, causing heating above 240°.

Warranty Coverage:

- Taramps guarantees its products against any defect in material or manufacturing process, provided that, at the discretion of its authorized technicians, it is found to be defective under normal conditions of use.
- The PRODUCT must contain the original label, on which its serial number is inserted.
- To use the warranty, the customer must present the invoice and the warranty term, both of which must contain the serial number on the product label.

Transport

Only products that fall under the terms of warranty coverage will have their transportation expenses covered, otherwise, the expense will be at the customer's expense.

WARRANTY CERTIFICATE

| NAME: | | | <u> </u> |
|------------|---------|--------|----------|
| ADDRESS: | | | |
| CITY: | | ZIP: | |
| STATE: | | FHONE: | |
| DEALER: | | | |
| ADDRESS: _ | | | |
| CITY: | | ZIP: | |
| STATE: | | PHONE: | |
| | | | |
| | INVOICE | NUMBER | |
| | | | |
| | | | |